

DATASHEET

Wi-Fi 7 M.2 A+E key Module **AW7990-AED**



Description

AW7990-AED is an Wi-Fi 7 BE3600 module with MediaTek MT7990AN chipset supports Wi-Fi 7 technology and feature IEEE802.11a/b/g/n/ac/ax/be compliant, 2.4GHz 2x2, 5GHz 3x3 2ss BE3600 Wi-Fi subsystem. The MT7990AN offers feature-rich wireless connectivity at high standards and delivers reliable, cost-effective throughput from an extended distance.

The optimized Wi-Fi baseband algorithms provide superb performance. The intelligent MAC design deploys a highly efficient offload engine and hardware data processing accelerators, which fully offload Wi-Fi task of the host processor. The MT7976CN is designed to support standard-based features in the areas of security, quality of service, and international regulations, giving end users the greatest performance at any time and in any circumstances.



Features

WLAN

- Wi-Fi compliant
- IEEE 802.11a, b, g, n, ac, ax, be compliant
- 2.4GHz 20 and 40 MHz, 2x2
- 5GHz: 20, 40, 80 and 160 MHz, 3x3 2ss
- Dual-Band Dual Concurrent (DBDC) iFEM
- Supports up to 4096-QAM
- Data rate of up to 688Mbps for 40MHz channel in 2.4Ghz and 2882Mbps for 160MHz in 5GHz mode
- Integrated power detector to support per packet Tx power control
- Multi-user multiple input multiple output (**MU-MIMO**) for Tx and Rx
- Multi-user Orthogonal Frequency-Division Multiple Access (**MU-OFDMA**) for Tx and Rx
- Support STBC, LDPC, Tx beamformer and Rx beamformee
- Support greenfield mode, mixed mode, and legacy mode

For more detailed information, please contact our sales team: sales@asiarf.com / +886 2 2940 7880

Copyright © AsiaRF All rights reserved. While every effort is made to ensure the information is accurate, AsiaRF does not accept liability for any errors or mistakes that may arise.

All specifications are subject to change without notice. AsiaRF Co., Ltd. | www.asiarf.com | +886 2 2940-7880 | sales@asiarf.com | Last Updated: 9/10/2025

